

SLAYER®



Single Group

This is the purist's machine. Slayer Espresso Single Group features the same commercial group, brew actuator, needle valve assembly, and steam valves as the 2-group and 3-group models—plus a few extras. With a touchscreen interface that assists in flavor profiling and temperature control, this one-group espresso machine has unprecedented capabilities.

Flavor Profiling

Manual operation of 3-position actuator allows total control.

Patented Needle Valve

Meter the introduction of water to the coffee bed for ultimate sweetness and syrupy body.

Pre-heat Coil

Stabilizes brew tank temperature.

Individual Brew & Steam Tanks

Pull a shot and steam milk simultaneously.

Touchscreen Menu

Modern, digital readout for brewing and programming.

Custom Options

Personalize with distinct body panel colors, metal finishes and wood sets (actuators, handles and cuprails).

Power Saver Schedule

Automatically powers on and off.

Shot Mirror

Improves visibility during extraction.



Essential Features

- Dual tank system with steam or brew tank priority
- PID temperature control, adjustable in 0.1° increments
- Electronic V3 grouphead rated to 1 million cycles
- Commercial portafilter with 58-millimeter, 18-gram basket
- Nanotech-coated precision shower screens
- Wood handles and actuators
- Hot water tap
- Non-slip feet
- Internal gear pump
- Direct plumb only

Specifications

- **Width:** 18.5 inches / 47 centimeters
- **Length:** 23 inches / 58 centimeters
- **Height:** 13 inches / 33 centimeters
- **Weight:** 110 pounds / 50 kilograms (tanks filled)
- **Brew tank:** 1.1 liters, 600 watts
- **Pre-heat coil:** 60 milliliters
- **Steam tank:** 3.3 liters, 1,300 watts OR 2,000 watts
- **Single-phase power:** 120 VAC, 50/60 Hz, 1.6 kW
- **Three-phase power (optional):** 220-240 VAC, 50/60 Hz, 2.1-2.4 kW

SLAYER
espresso machines

+1 206 284 7171 6133 6TH AVE. S., SEATTLE, WA 98108 - USA SALES@SLAYERESPRESSO.COM SLAYERESPRESSO.COM

OCTOBER 9, 2019